

HYPHONE

www.hyphone.com.tw

INTRODUCTION

2" (3") Pistol Angle Sander

Powerful & Easy Handling



HY-1582A

HY-1582C

HY-1582E

Specification	HY-1582A	HY-1582C	HY-1582E
Application	Mini Sanding/Stripping/Polishing Sander		
Power (hp)	0.35		
Pad size	2" or 3" (Velcro)		2" or 3" (Roloc)
Orbit	3 mm	none	
Trigger Style	Push button		
Spindle	5/16" - 24 UNF		1/4"-20
Free speed (rpm)	16,000	20,000	
Exhaust	Side swivel collar		
Vibration (m/s ²)	4.72	1.94	
Sound pressure / power	80 / 91 dBA		
Weight	1.52 lb / 0.69 Kg	1.47 lb / 0.67 Kg	1.54 lb / 0.7 Kg
Length (with Pad)	4.7 " / 120 mm	4.1 " / 103 mm	4.9 " / 124 mm
Air consumption @ 90psi	3.1 cfm / 88 L/min		
Air inlet in.	1/4"		
Minimum hose size	3/8" (10mm)		

Hyphone Machine Industry

TEL:886-4-2563-3678

21, Lane 742, Sec 1 , He-Mu Rd. Shen Gang Dist.

Taichung, Taiwan